



LOGIPIX 4TH GEN. T OUTDOOR NVR

The Logipix 4th generation T Outdoor NVR is the high speed network video recorder of the Logipix solutions that was specially developed for on-site recording tasks. Thanks to its massive outdoor enclosure with an IP66 rating, it is able to cope with even extreme weather conditions. The thermal control of the electronic components relies on a combined system of integrated heat pipes and fans, a thermoelectric peltier cooler and sunshields. The device serves the Logipix 20MP Camera and reliably performs the recording of their high-quality video streams. The built-in Logipix Video Content Analysis functions that makes automatic traffic violation possible.

KEY FEATURES

- Built-in Video Content Analysis functions
- Intelligent image transmission
- Semi-passive and active cooling system
- Fans and sun shields

- IP66 box-mount, outdoor enclosure
- Designed to work reliably in outdoor conditions
- Built-in RAID function
- VRM[™] Fail-safe file system



Part number	I NVR4-O-4-4-12
escription	Logipix Outdoor Network Video Recorder
pplication	Logipix Traffic Violation Detection Solution
lumber of Cameras	4 pcs Logipix 20 MP Traffic cameras
umber of HDDs	4
CPU board	Linux Operating System
	6 Cores 3.4GHz CPU
	Diskless operation
letwork	4 x 1GBit Ethernet for camera, 1 x 1GBit Ethernet for monitoring
letwork security	2048 bit public-key RSA; User authentication
Storage	4 SATA HDD
	VRM™ Failsafe File-system
	Built-in RAID function
Cooling system	Active cooling system
	Heat pipes, peltier, fan and sunshield
ntelligence	Integrated Video Content Analysis
Approvals	EN 55032:2015/AC:2016, EN 61000-3-2:2014, EN 61000-3-3:2013,
	EN 50130-4:2011/A1:2015, IEC/EN 60529 IP66, IEC 60950-1

ELECTRICAL SPECIFICATION		
Operating temperature	-30°C – 55°C (-22°F to +131°F)	
Supply voltage	230 V AC	
Inrush current	20 A	
Current consumption	max. 4.5 A	
Power consumption	200 W + 250 W cooling	
Humidity	up to 100% RH (condensing)	
Protection classification	IP66	

MECHANICAL SPECIFICATION	
Weight	30 kg (66.1 lbs)
Dimensions (W × D × H)	440 × 232 × 672 mm
Package gross weight	34 kg (75 lbs)
Package dimensions	575 × 350 × 800 mm

RELATED COMPONENTS

Logipix CAMERAS

Part number	Description
LPIX20-T-DNI-I0XX	Logipix 20 Megapixel Traffic camera
LPIX20-T-DNI-I1XX	Logipix 20 Megapixel Traffic bullet camera
LPIX20-E-XX	Logipix Evidence camera

Logipix SOFTWARE

Part number	Description
LTS	Traffic Violation Detection Software
LHS	Highway Software



APPLICATION AREAS

Logipix 4th generation T Outdoor NVR has been designed to perform recording, Video Content Analysis and image transmission tasks for the Logipix Traffic solution. The device is able to automatically detect several types events based on the high resolution image of Logipix 20 MP Panorama camera. All VCA detection applications are license-dependent. Thanks to its IP66-rated outdoor enclosure and flexible cooling system the Logipix NVR Outdoor is capable of working reliably even in the most extreme weather conditions.

Logipix Traffic solution

Logipix Highway Solution

DIMENSIONS (all values are in mm)



